

Stelvio right side tool tube mount installation instructions

Hardware included:

Qty (1) stainless steel bracket for mounting tool tube

Qty (1) large tool tube

Qty (2) M6x1x40mm flathead stainless cap screw (cross bar spool mount)

Qty (6) M6x1x35mm flathead stainless cap screw (regular spool mount)

Qty (3) M6x3mm thick spacer (between bracket and rack)

Qty (3) M6x1x16mm button head stainless cap screw (tube to bracket)

Qty (3) M6 flat washers (tube to mount)

Qty (15) M6x1 nylock nuts

Step (1)- Left side rack, replace all spool hardware. Remove standard (black) hardware on three spools with 35mm long fasteners. The remaining spool hardware that contains the crossbar is replaced with the 40mm fastener. Use supplied nylock nuts and tighten.

Step (2)- See PHOTO #1 Mount tool tube to bracket using (3) 16mm fasteners through the bracket, mount tube, fit washers, attached nylock nuts. Washers fit between tube and nylock nut.

Step (3)- See PHOTO #2 Remove right side rack hardware, place 35mm long fasteners in all spool locations except cross bar, place 40mm hardware at cross bar. Add spacers to all 35mm fasteners except cross bar, place tube/bracket in place, use nylock nuts to secure. Spacers keep tool tube parallel to luggage rack.

Step (4)- See PHOTO #3 Proper installation of spacer with rack.



PHOTO #1

Tube mounted on bracket in proper direction.



PHOTO #2

Tool tube mounted in place



PHOTO #3

Proper location of rack, spacer, bracket, and nut.