

Procedure for the duplication of the remote control for "Piaggio KeyLess" system.

A= Remote control

B = TAG with integrated transponder

1. Check the initial conditions:

1.1 Battery voltage higher than > 12V.

1.2 It is necessary to have the TAG with integrated transponder.

1.3 It is necessary to have all remote controls to be coded (including those already coded before the procedure),

1.4 It is necessary to connect the PADS diagnosis tool to the OBD connector of the vehicle, using a specific tool.

Specific tooling

020922Y

Diagnosis Tool

021017Y

EOBD E5 diagnostics cable

2. Start duplication procedure before entering Keyless Self-diagnosis using PADS:

2.1 Ignition key on "**OFF**",

2.2 Deactivate the remote control by pressing the first and the second button.

2.3 Press the ignition switch and at the same time bring the TAG close to the Keyless control unit. (*)

2.4 Following the flashing of the hazard warning lights, the ignition key can be turned to "**ON**" (**)

(*) THE TAG has a built-in transponder and must be brought into contact with the top internal side of the leg shield back plate, to the left, where the keyless control unit is located.

() From the moment the selector is turned to the "ON" position, the Remote Control Programming procedure must be started within 120 seconds (description in step 3. Otherwise, the procedure must be started from step 2.**