



SPECIFICATION CARD

Art no	FKA 115	Rev	0
Date	2022-05-25		
Sign	DN		

Replaces	Type
	30 mm open cartridge

Changes

Brand	Model		Position
Aprilia	Tuareg 660		Front
Total length front fork	Stroke metal	Total length cartridge	
944 mm	240 mm	936 mm	

Compression setting	Rebound setting		
NIX30 adventure 1.1 C5	NIX30 adventure 1.1 R5		
1 Primary shim stack	1 Primary shim stack		
00185-26	00185-26		
2	2		
00185-24	00185-24		
3	3		
00185-20	00185-22		
4	4		
00185-18	00185-20		
5	5		
00185-16	00186-18		
6	6		
00185-51 + 00186-51	00186-16		
	7		
	00188-51		
1 Secondary shim stack			
01415-22			
2			
01415-20			
3			
01415-18			
4			
01420-16			
5			
01420-14			
6			
01420-12			
7			
01430-10			

Main spring (length/rate N/mm)	Top out rubber (engagement)	Suspension fluid	Compression adjustment
08438-55 (450/5.5)	21752-01 (5)	01309	14 clicks
Main spring preload	Fork leg position	Suspension fluid level	Rebound adjustment
0 mm	Standard	120 mm	14 clicks
Assy drawing no	Notes		Order no
FKA 115			Quantity
Assy instruction drawing no			Delivery week
FKA 100			
Process inspection sheet			
FKA 115			