



SHOCK ABSORBER T36 SPECIFICATION CARD

Art no	AP 468 0
--------	-----------------

Brand Aprilia	Model RSV4	Year 2017	Date 2017-10-20
Total length 315 (+2/-4)	Stroke 63	Type T36PR1C1LB	

Cylinder head 21896-01	Body (Length 101) 21011-06 + 21006-06	Shaft (Length 162) 64103-13 + 21020-20	End bracket 03110-12 + 01059-07
Reservoir tube (Size 44/80) 00302-06	Reservoir top --	Internal spacers (Thickness 5) 21028-05	Hose --
Gas piston 00305-01	Shaft jet --	Adjustment valve --	Valve stop 21848-12
Piston 21015-10	Adjustment shaft --	Topout spring (8x150) 21031-06	Seal head 21025-05

Compression setting C45	Rebound setting R5		Hose fitting code
Adjuster + valve 21049-60 + 21044-60	Adjuster + valve 21049-61 + 21044-37		Sticker fitting code 4/2/0/1/1/1
Check valve spring 21146-50	Check valve spring 21146-15		Hose fitting code hydr p-l adj
1 01420-22	1 01425-22		Sticker fitting code hydr p-l adj
2 01420-20	2 01425-20		Assy drawing no AP 468
3 01420-18	3 01425-18		Assy Instruction drawing no 03520-06
4 01420-16	4 01425-16		Process inspection sheet General
5 01420-14	5 01425-14		Process inspection drawing
6 01420-12	6 01425-12		Mounting instruction customer AP 468
7 01415-10	7 01415-09		
8 01449-06	8 01449-06		
9	9		

Spring (Free length 160) 21040-26 (85 N/mm)	Preload 12 (+5/-3)	Bearing cylinder head 00536-13	Bearing end bracket 00536-13	
Preload adjuster (Hydraulic) 21681-01(81)	Spring clip 21036-04	Spacers cylinder head 01218-33 (10x23)	Spacers end bracket 01218-46 (10x36)	
Preload adjuster bracket --	Preload adjuster position 2,4 (3,2 conical nut)	Bump rubber 21029-01 (19)	Comp clicks 10	Reb clicks 14
Replaces	Notes Shim stack + clamp must be 3.3±1 mm thick		Oil art no 01309-XX	Filling pressure 6 Bar
Changes	Dividing piston position: 7±1 mm		Sign NB	
			Order no	
			Quantity	
	Dyno file		Delivery week	