



SHOCK ABSORBER T36 SPECIFICATION CARD

Art no	AP 468 3
Date	2020-08-01

Brand	Aprilia	Model	RSV4	Year	2017
Total length	315 (+2/-4)	Stroke	63	Type	T36PR1C1LB

Cylinder head	21896-01	Body (Length 101)	21011-06 + 21006-06	Shaft (Length 162)	64103-13 + 21020-20	End bracket	03110-12 + 01059-07
Reservoir tube (Size 44/80)	00302-06	Reservoir top	--	Internal spacers (Thickness 5)	21028-05	Hose	--
Gas piston	00305-01	Shaft jet	--	Adjustment valve	--	Valve stop	21848-12
Piston	21015-10	Adjustment shaft	--	Topout spring (8x150)	21031-06	Seal head	21025-05

Compression setting	C45	Rebound setting	R5		Hose fitting code	
Adjuster + valve	21049-60 + 21044-60	Adjuster + valve	21049-61 + 21044-37		Sticker fitting code	4/2/0/1/1/1
Check valve spring	21146-50	Check valve spring	21146-15		Hose fitting code hydr p-l adj	
1	01420-22	1	01425-22		Sticker fitting code hydr p-l adj	
2	01420-20	2	01425-20		Assy drawing no	AP 468
3	01420-18	3	01425-18		Assy Instruction drawing no	03520-06
4	01420-16	4	01425-16		Process inspection sheet	General
5	01420-14	5	01425-14		Process inspection drawing	
6	01420-12	6	01425-12		Mounting instruction customer	AP 468
7	01449-03 (10 mm)	7	01449-02 (9 mm)			
8		8				
9		9				

Spring (Free length 160)	21040-26 (85 N/mm)	Preload	12 (+5/-3)	Bearing cylinder head	00536-04	Bearing end bracket	00536-04		
Preload adjuster (Hydraulic)	21686-01(81)	Spring clip	21036-14	Spacers cylinder head	01218-33 (10x23)	Spacers end bracket	01218-46 (10x36)		
Preload adjuster bracket	--	Preload adjuster position	2,4 (3,2 conical nut)	Bump rubber	21029-01 (19)	Comp clicks	10	Reb clicks	14
Replaces	AP 468 2 2019-02-28	Notes	Shim stack + clamp must be 3.3±1 mm thick Dividing piston position: 7±1 mm			Oil art no	01309-XX	Filling pressure	6 Bar
Changes	21686-01(81) was 21681-01(81). 21036-14 was 21036-04.	Dyno file				Sign	NB		
					Order no				
					Quantity				
					Delivery week				