

## Motorbike 4T SAE 15W-50 Street

### Description

High-performance motor oil based on fully synthetic technology. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. Tested on engines with catalytic converters.

### Properties

- optimum stability to aging
- guarantees low oil consumption
- especially suitable for wet clutches
- tested for catalytic converters
- outstanding engine cleanliness
- optimum lubrication under all operating conditions
- high wear resistance
- high shear stability

### Specifications and approvals:

API SN Plus • JASO MA2

### Technical data

SAE class (engine oils)	15W-50 SAE J 300
Density at 59 °F	0,870 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	140,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	18,3 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -13 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -4 °F (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	145 DIN ISO 2909
HTHS at 302 °F	>= 3,7 mPas ASTM D5481
Pour point	-22 °F DIN ISO 3016
Evaporation loss (Noack)	10,6 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575



### Technical data

Color number (ASTM)	L 2,5
	DIN ISO 2049

### Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

### Application

The operating instructions of the engine manufacturers must be followed.

**Observe: Optimum effectiveness only when the product is used on its own (i.e. no mixing).**

### Available pack sizes

1 l Canister plastic	20058 USA AND CANADA (-EN-F-)
4 l Canister plastic	20060 USA AND CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**